

Flash Memory Storage Solutions From the Worldwide Flash Card Leader.



More people rely on SanDisk® memory cards than any other brand in the world, and for good reasons. As a pioneer and leader in the field, SanDisk designs its own non-volatile flash memory and controller technology, and develops the complete card design and manufacturing process. By having this capability, staying very close to the customers and meeting the needs of the markets served, SanDisk is able to continually set the standard for quality, reliability and performance.



	CompactFlash	SanDisk Ultra II CompactFlash		
Interface	PC Card ATA True IDE Mode	PC Card ATA True IDE Mode		
Performance (Notes 1 & 2) Interface Transfer Speed (Max)	16.6 MB/sec	16.6 MB/sec		
Power Requirements (Note 1) DC Input Voltage Commercial Industrial	3.3V ± 5%, 5V ± 10% 3.3V ± 5%, 5V ± 10%	3.3V ± 5%, 5V ± 10% 3.3V ± 5%, 5V ± 10%		
Typical Power Dissipation (Notes 3 & 4) Sleep Read (Typical) Write (Typical)	300 µA (3.3V) <50 mA RMS (3.3V) <65 mA RMS (3.3V)	500 µA (5V) <55 mA RMS (5V) <70 mA RMS (5V)	300 µA (3.3V) <50 mA RMS (3.3V) <65 mA RMS (3.3V)	500 µA (5V) <55 mA RMS (5V) <70 mA RMS (5V)
Environmental Specifications Temperature Operating Commercial Non-Operating Commercial	0–60°C –25–85°C	0–60°C –25–85°C		
Humidity Operating Non-Operating	8–95%, non-condensing 8–95%, non-condensing	8–95%, non-condensing 8–95%, non-condensing		
Acoustic Noise (at 1 meter)	0 dB	0 dB		
Vibration Operating Non-Operating	15 G peak to peak max. 15 G peak to peak max.	15 G peak to peak max. 15 G peak to peak max.		
Shock Operating Non-Operating	2,000 G max. 2,000 G max.	2,000 G max. 2,000 G max.		
Altitude (relative to sea level) Operating/Non-Operating	80,000 feet max.	80,000 feet max.		
Reliability and Maintenance MTBF (Mean Time Between Failures) Preventive Maintenance Data Reliability	>1,000,000 hours None <1 non-recoverable error in 10 ¹⁴ bits read	>1,000,000 hours None <1 non-recoverable error in 10 ¹⁴ bits read		
Physical Specifications Length Width Thickness (Body) Thickness (Removable Edge) Weight	CompactFlash 1.433 in (36.4 mm) 1.685 in (42.8 mm) 0.130 in (3.30 mm) 0.155 in (3.94 mm) 0.40 oz (11.4 g)	Ultra II CompactFlash 1.433 in (36.4 mm) 1.685 in (42.8 mm) 0.130 in (3.30 mm) 0.155 in (3.94 mm) 0.40 oz (11.4 g)		
Ordering Information Order Model	SDCFJ-YYY	SDCFH-YYY		
YYY:	64 64.2 MB 128 128.4 MB 256 256.9 MB 512 512.4 MB 1024 1024.9 MB 2048 2048.9 MB 4096 4096.3 MB	256 256.2 MB 512 512.4 MB 1024 1024.9 MB 2048 2048.9 MB 4096 4096.3 MB 8192 8192.6 MB		

Specifications subject to change without notice

Other versions available:

B: Standard
H: "Ultra" High-Speed
J: MLC/NAND
I: Industrial Temperature

Note: Capacities may vary by product family. Consult your SanDisk Sales Representative for correct ordering part numbers.

Note 1: All values quoted are typical at ambient temperature and nominal supply voltage unless otherwise stated.

Note 2: All performance timing assumes the controller is in the default (i.e., fastest) mode.

- **SanDisk CompactFlash®**

SanDisk CompactFlash revolutionized handheld electronics with unprecedented functionality when CompactFlash was first invented. The CompactFlash memory card's matchbook size and half-ounce weight make it the ideal solution for small devices that need high capacity flash memory. Today, the CompactFlash storage specification is the industry-standard for next-generation, small form factor consumer applications such as digital cameras and handheld PCs that need very high capacities. CompactFlash is available in capacities up to 4GB* and the SanDisk Ultra® II CompactFlash is available in capacities up to 8GB.



- **SanDisk MultiMediaCard™**

The SanDisk MultiMediaCard is available in 32MB, 64MB, 128MB, and 256MB capacities. Weighing less than two grams and about the size of a postage stamp, the SanDisk MultiMediaCard is designed to meet the unique requirements of portable communications and computing markets for small size, upgradable capacities, and low cost.



- **SanDisk RS-MMC™
(Reduced-Size MultiMediaCard)**

The SanDisk RS-MMC is designed for use in the newest generation of ultra-small mobile phones. It is about half the size of a standard MultiMediaCard, and has the same simple, low power interface. This allows the RS-MMC to be used with an extender in a full size MMC slot. The RS-MMC is available in 32MB, 64MB, 128MB, 256MB and 512MB capacities.



* 1 megabyte (MB) = 1 million bytes;
1 gigabyte (GB) = 1 billion bytes

- **SanDisk Memory Stick PRO Duo™ Card**

The SanDisk Memory Stick PRO Duo card provides high capacity memory with the data transfer speeds of the Memory Stick PRO Interface. It was designed for use in the newest generation of mobile phones, digital still cameras, video cameras, digital music players and other size-sensitive mobile devices. The Memory Stick PRO Duo cards are also very secure with Advanced MagicGate™ copy protection included. Available in 32MB, 64MB, 128MB, 256MB, 512MB and 2GB capacities.



- **SanDisk TriFlash®**

SanDisk TriFlash is a single chip device ideal for storing audio, video, images and other data on small portable systems such as smart phones, MP3 players and handheld computers. It has a simple, high-performance serial interface that follows the industry standard SPI, MultiMediaCard, or SD card protocols. This allows the TriFlash to be seamlessly integrated into designs that already have a memory card slot. TriFlash is available today in 64MB, 128MB, 512MB and 1GB capacities.



- **SanDisk USB Flash Drive (UFD)**

The SanDisk UFD is available in 64MB, 128MB, 256MB, 512MB, 1GB and 2GB capacities. It is Hi-Speed USB 2.0 compliant. This drive was specifically designed to allow unique customization on the label. The SanDisk UFD is slim enough to plug into any USB port without obstructing adjacent ports.



	microSD	SD Card
Interface	SD or SPI	SD or SPI
Performance (Notes 1 & 2)		
Interface Transfer Speed (Max)	12.5 MB/sec	12.5 MB/sec
Power Requirements (Note 1)		
DC Input Voltage		
Commercial	2.7V to 3.6V	2.7V to 3.6V
Industrial	N/A	N/A
Typical Power Dissipation (Notes 3 & 4)		
Sleep	150 μ A max.	250 μ A
Read	<45 mA max.	<75 mA
Write	<50 mA max.	<75 mA
Environmental Specifications		
Temperature		
Operating Commercial	-25–85°C	-25–85°C
Operating Industrial	N/A	N/A
Non-Operating Commercial	-40–85°C	-40–85°C
Non-Operating Industrial	N/A	N/A
Humidity		
Operating	25°C/85% rel. humidity	25–95%, non-condensing
Non-Operating	40°C/85% rel. humidity	25–95%, non-condensing
Acoustic Noise (at 1 meter)	0 dB	0 dB
Vibration		
Operating	15 G peak to peak max.	15 G peak to peak max.
Non-Operating	15 G peak to peak max.	15 G peak to peak max.
Shock		
Operating	1,000 G max.	1,000 G max.
Non-Operating	1,000 G max.	1,000 G max.
Altitude (relative to sea level)		
Operating/Non-Operating	80,000 feet max.	80,000 feet max.
Reliability and Maintenance		
MTBF (Mean Time Between Failures)	>1,000,000 hours	>1,000,000 hours
Preventive Maintenance	None	None
Data Reliability	<1 non-recoverable error in 10^{16} bits read	<1 non-recoverable error in 10^{16} bits read
Physical Specifications		
Length	11 mm	32 mm \pm 0.1 mm
Width	15 mm	24 mm \pm 0.08 mm
Thickness (Body)	1.0 mm	2.1 mm \pm 0.1 mm
Thickness (Removable Edge)	N/A	N/A
Weight	0.40 g. max.	2.0 g. max.
Ordering Information		
Order Model #	SDSDQ-YYY	SDSDJ-YYY
YYY:	32 32 MB 64 64 MB 128 128 MB 256 256 MB 512 512 MB	64 64.2 MB 128 128.2 MB 256 256.2 MB 512 512.4 MB 1024 1024.9 MB 2048 2048.9 MB

Specifications subject to change without notice

Note 1: All values quoted are typical at ambient temperature and nominal supply voltage unless otherwise stated.

Note 2: All performance timing assumes the controller is in the default (i.e., fastest) mode.

	SanDisk Ultra II SD Card	MiniSD
Interface	SD	SD or SPI
Performance (Notes 1 & 2) Interface Transfer Speed (Max)	12.5 MB/sec	12.5 MB/sec
Power Requirements (Note 1)		
DC Input Voltage		
Commercial	2.7V to 3.6V	2.7V to 3.6V
Industrial	N/A	N/A
Typical Power Dissipation (Notes 3 & 4)		
Sleep	250 μ A	150
Read	<75 mA	<45 mA
Write	<75 mA	<50 mA
Environmental Specifications		
Temperature		
Operating Commercial	-25–85°C	-25–85°C
Operating Industrial	N/A	N/A
Non-Operating Commercial	-40–85°C	-40–85°C
Non-Operating Industrial	N/A	N/A
Humidity		
Operating	25–95%, non-condensing	8–95%, non-condensing
Non-Operating	25–95%, non-condensing	8–95%, non-condensing
Acoustic Noise (at 1 meter)	0 dB	0 dB
Vibration		
Operating	15 G peak to peak max.	15 G peak to peak max.
Non-Operating	15 G peak to peak max.	15 G peak to peak max.
Shock		
Operating	1,000 G max.	1,000 G max.
Non-Operating	1,000 G max.	1,000 G max.
Altitude (relative to sea level)		
Operating/Non-Operating	80,000 feet max.	80,000 feet max.
Reliability and Maintenance		
MTBF (Mean Time Between Failures)	>1,000,000 hours	>1,000,000 hours
Preventive Maintenance	None	None
Data Reliability	<1 non-recoverable error in 10^{14} bits read	<1 non-recoverable error in 10^{14} bits read
Physical Specifications		
Length	32 mm	21.5 mm
Width	24 mm \pm 0.08 mm	20.0 mm
Thickness (Body)	2.1 mm \pm 0.1 mm	1.4 mm
Thickness (Removable Edge)	N/A	N/A
Weight	2.0 g. max.	1.0 g. max.
Ordering Information		
Order Model #	SDDSH-YYY	SDDSM-YYY
YYY:	512 512 MB 1024 1024.9 MB 2048 2048.9 MB	16 16.1 MB 32 32.1 MB 64 64.2 MB 128 128.2 MB 256 256.2 MB 512 512.4 MB 1024 1024.9 MB

Specifications subject to change without notice

Note 3: Sleep mode currently is specified under the condition that all card inputs are static CMOS levels and in a "Not Busy" operating state.

Note 4: The currents specified show the bounds of programmability of the product.

SanDisk offers a broad range of flash data storage products, including PC cards, memory modules, CompactFlash®, SD™, miniSD, MultiMediaCard™, xD™, RS-MMC™, OEM USB and Memory Stick PRO Duo™. All of these products share the leading edge technology for which SanDisk is known.

SanDisk is the inventor or co-developer of most of the flash memory card form factors on the market today, including CompactFlash, MultiMediaCard, SD, Memory Stick PRO™, TriFlash and microSD.

In 2000, SanDisk entered into a joint flash fabrication venture called FlashVision LLC, which produces NAND wafers at a plant located in Yokkaichi, Japan. In 2002, SanDisk launched the world's first Multi-Level Cell NAND-based flash memory products, and today SanDisk is one of only two companies manufacturing MLC NAND flash memory.

Beyond the core flash memory technology, SanDisk continues to evolve flash card functionality and performance levels to meet the needs of emerging applications such as mobile phones, PDAs, portable audio, digital video, digital imaging and more. This brochure highlights all of the products currently available for OEM customers. For more accurate and up-to-date product information and specifications, please visit the SanDisk website at www.sandisk.com.

• SanDisk microSD™ Card

Measuring just 11mm by 15mm and 1mm thick, the new SanDisk microSD card is the ultimate storage solution for the next generation of increasingly compact mobile phones. Two-thirds the size of a SIM module, microSD cards are even smaller than many embedded memory devices.



Available in capacities ranging from 32MB to 512MB, the SanDisk microSD card gives mobile phone designers and manufacturers more flexibility. In addition, the SanDisk microSD removable card makes it easy for mobile phone users to transport their personal content like contact lists and saved photos, high fidelity ring tones, applications, and system settings from one mobile phone to another when they need to upgrade their phone or service.

• SanDisk SD™ Card

The SD Card is a flash memory storage device designed to meet the security, capacity and performance requirements inherent in the latest consumer electronics devices. Key enhancements over the MultiMediaCard include cryptographic security for protection of copyrighted data, more than a 5X improvement in maximum data transfer rate, and a user selectable write protect switch on the card casing. The standard SD is offered in capacities from 64MB to 2GB and the SanDisk Ultra II SD is available in 512MB and 1GB capacities.



• SanDisk miniSD™ Card

The miniSD card is the world's smallest removable flash storage card, designed specifically to meet the needs of today's small mobile phones. SanDisk miniSD is based on the popular SD card. It uses the same powerful, simple, high performance interface SD offers. The miniSD offers full compatibility and interoperability with any SD host by using an available passive adapter. The SanDisk miniSD card is available in capacities up to 1GB.



	MultiMediaCard	RS-MMC
Interface	MultiMediaCard or SPI	MultiMediaCard or SPI
Performance (Notes 1 & 2)		
Interface Transfer Speed (Max)	2.5 MB/sec	2.5 MB/sec
Power Requirements (Note 1)		
DC Input Voltage		
Commercial	2.7V to 3.6V	2.7V to 3.6V
Industrial	N/A	N/A
Typical Power Dissipation (Notes 3 & 4)		
Sleep	150 μ A	150 μ A
Read	<50 mA	<50 mA
Write	<60 mA	<60 mA
Environmental Specifications		
Temperature		
Operating Commercial	-25-85°C	-25-85°C
Operating Industrial	N/A	N/A
Non-Operating Commercial	-40-85°C	-40-85°C
Non-Operating Industrial	N/A	N/A
Humidity		
Operating	8-95%, non-condensing	8-95%, non-condensing
Non-Operating	8-95%, non-condensing	8-95%, non-condensing
Acoustic Noise (at 1 meter)	0 dB	0 dB
Vibration		
Operating	15 G peak to peak max.	15 G peak to peak max.
Non-Operating	15 G peak to peak max.	15 G peak to peak max.
Shock		
Operating	1,000 G max.	1,000 G max.
Non-Operating	1,000 G max.	1,000 G max.
Altitude (relative to sea level)		
Operating/Non-Operating	80,000 feet max.	80,000 feet max.
Reliability and Maintenance		
MTBF (Mean Time Between Failures)	>1,000,000 hours	>1,000,000 hours
Preventive Maintenance	None	None
Data Reliability	<1 non-recoverable error in 10^{14} bits read	<1 non-recoverable error in 10^{14} bits read
Physical Specifications		
Length	32 mm	18 mm
Width	24 mm	24 mm
Thickness (Body)	1.4 mm	1.4 mm
Thickness (Removable Edge)	N/A	N/A
Weight	1.8 g. max.	1.0 g. max.
Ordering Information		
Order Model #	SDMJ-YYY	SDMRJ-YYY
YYY:	32 32.1 MB 64 64.2 MB 128 128.2 MB 256 256.9 MB	64 64.2 MB 128 128.2 MB 512 512.4 MB

Specifications subject to change without notice

Note 3: Sleep mode currently is specified under the condition that all card inputs are static CMOS levels and in a "Not Busy" operating state.

Note 4: The currents specified show the bounds of programmability of the product.



	Memory Stick PRO Duo		TriFlash
Interface	Memory Stick PRO		MultiMediaCard SD or SPI
Performance (Notes 1 & 2) Interface Transfer Speed (Max)	20 MB/sec		12.5 MB/sec
Power Requirements (Note 1)			
DC Input Voltage			
Commercial	2.7V to 3.6V		2.7V to 3.6V
Industrial	N/A		N/A
Typical Power Dissipation (Notes 3 & 4)	Typical	Max	
Sleep	125 µA	1 mA	150 µA max.
Read	<50 mA	65 mA	<45 mA max.
Write	<75 mA	100 mA	<50 mA max.
Environmental Specifications			
Temperature			
Operating Commercial	-25–85°C		-25–85°C
Operating Industrial	N/A		N/A
Non-Operating Commercial	-40–85°C		-40–85°C
Non-Operating Industrial	N/A		N/A
Humidity			
Operating	25–85%, non-condensing		8–95%, non-condensing
Non-Operating	Max 95% (saturated state)		8–95%, non-condensing
Acoustic Noise (at 1 meter)	0 dB		0 dB
Vibration			
Operating	15 G peak to peak max.		15 G peak to peak max.
Non-Operating	15 G peak to peak max.		15 G peak to peak max.
Shock			
Operating	1,000 G max.		1,000 G max.
Non-Operating	1,000 G max.		1,000 G max.
Altitude (relative to sea level)			
Operating/Non-Operating	80,000 feet max.		80,000 feet max.
Reliability and Maintenance			
MTBF (Mean Time Between Failures)	>1,000,000 hours		>1,000,000 hours
Preventive Maintenance	None		None
Data Reliability	<1 non-recoverable error in 10 ¹⁴ bits read		<1 non-recoverable error in 10 ¹⁴ bits read
Physical Specifications			
Length	20 mm		12 mm (64/128/256 MB) 10 mm (32 MB)
Width	31 mm		18 mm (64/128/256 MB) 12 mm (32 MB)
Thickness (Body)	1.6 mm		1.2 mm max.
Thickness (Removable Edge)	N/A		N/A
Weight	2.0 g. max.		0.35g (64/128/256 MB) 0.20g (32 MB)
Ordering Information			
Order Model #	SDMSPC-YYY	SDMSPD-YYY	SDQXAJHP-YYY
Where X:			S = SD interface
YYY:	32 32.1 MB	64 64 MB 128 128 MB 256 256 MB 512 512 MB	SDQSAJHL-YYY 32 32 MB SDQSAJHL-YYY 64 64 MB 128 128 MB 256 256 MB 512 512 MB 1024 1024 MB

Specifications subject to change without notice

SouthWest USA & Mexico
140 Caspian Court
Sunnyvale, CA 94089
Phone: 760-736-8000

**Eastern/North Central USA
& Central/South America**
134 Cherry Creek Circle
Winter Springs, FL 32708
Phone: 407-366-6490
Fax: 407-366-5945

**NorthEastern USA
& Canada**
620 Herndon Pkwy
Suite 200
Herndon, VA 22070
Phone: 703-481-9828
Fax: 703-437-9215

Europe
Schipholpoort 40
2034 MB Haarlem
The Netherlands
Phone: +31-23-551-4227
Fax: +31-23-532-5721

Central & Southern Europe
Rudolf-Diesel-Str. 3
40822 Mettmann, Germany
Phone: 49-210-495-3433
Fax: 49-210-495-3434

Korea
#14-202, Anyang International
Distribution Complex,
555-9 Hogye-dong, Dongan-gu
Anyang City, Kyounggi-Do
Phone: +82-31-479-0507
Fax: +82-31-479-0509

Japan
Nisso 15 Bldg. 8F
2-17-19 Shin-Yokohama,
Kohoku-ku
Yokohama 222-0033
Phone: 81-45-474-0181
Fax: 81-45-474-0371

Asia/Pacific Rim
Suite 902 - 903
Bank of East Asia Harbour View Centre
56 Gloucester Road
Wanchai
Hong Kong
Phone: 852-2712-0501
Fax: 852-2712-9385

